



## **OSEC®-B HYPOCHLORITE GENERATION SYSTEM**

### **WALLACE & TIERNAN® PROCESS SYSTEMS**

The OSEC®-B electro-chlorinator was developed for the generation of sodium hypochlorite through the electrolysis of a brine solution. Production of sodium hypochlorite solution takes place in membraneless, single-pass cells.

#### **APPLICATIONS**

- Potable water
- Swimming pool water
- Water in breweries, the beverage and food industry
- Cooling water
- Irrigation systems
- Municipal and industrial wastewater

Electrolysers built to the tubular cell process, which are used as an alternative to chlorine gas systems, provide many safety features. Risks inherent in the transport, handling and storage of chlorine gas or commercial sodium hypochlorite solutions are eliminated. Local regulatory issues often limit the use of chlorine gas for safety reasons.

#### **FEATURES**

- Facility to meter solution to multiple points of application
- PLC controlled system
- Capacities up to 40 kg/h Cl<sub>2</sub>

OSEC® systems provide for on-site, on-demand production of sodium hypochlorite solution from salt, water, and electricity. Generation takes place on demand only. The sodium hypochlorite solution produced in batch operation retains its strength even if it is stored over an extended period of time.

#### **Key Benefits**

- Highly economical due to convenient brine solution and low energy consumption
- Rugged system with long life anodes, reliable process and compact construction
- Virtually operator-free performance due to programmed electrode cleaning cycle
- Easy installation and start-up

The anodes used are made from titanium with a precious metal coating and carries a five year warranty after installation and commissioning. The cathodes are made from a special grade Hastelloy® C alloy. Automatic control of the supply voltage combined with a programmable periodic cleaning cycle of the monopolar electrodes by dilute hydrochloric acid ensure a virtually operator-free performance. The number of anodes in the electrolyser can be customised to produce the desired quantity of chlorine. This system flexibility provides a significant reduction in power requirements and plant cost. A PLC control system provides for the fully automatic operation of the unit including all control, monitoring, alarm and interlock functions. Having set the flow rates for brine and dilution water, all that remains on site is to turn the start switch. Metering of the sodium hypochlorite solution is achieved by manually or automatically controlled dosing pumps.

## OPERATION

Softened water is mixed with common salt (tablets) in a dissolving tank to prepare a saturated brine solution which is then fed by a metering pump into the electrolyser cell. The salt saturator is designed to allow refilling of salt without interrupting the generating process. The dilution water is combined with the saturated brine solution to form an approximately 2% brine solution which enters the electrolyser. The DC current applied produces sodium hypochlorite and hydrogen. Heat transfer and the formation of gas result in a lifting effect that accelerates the separation of the hydrogen from the electrolyte. The hydrogen together with the sodium hypochlorite solution is discharged into the product storage tank. An air blower is used to dilute the hydrogen to well below its flammability limit and to force ventilate it to a safe outdoor discharge point. The sodium hypochlorite solution produced has a strength of 6 g/l equivalent chlorine. Level probes installed in the sodium hypochlorite solution storage tank start and stop the electrolyser.

## TECHNICAL DATA

### Capacity ranges of the electrolyser:

570, 1330, 2660 g/h, 5 and 10 kg/h Cl<sub>2</sub> (for systems up to 40 kg/h Cl<sub>2</sub>: consult)

**Power consumption:** 4 – 5 kWh per kg chlorine

**Salt consumption:** approx. 3 kg salt per kg chlorine

### Sodium hypochlorite strength:

approx. 6 g/l equivalent chlorine

**Dimensions (W x H x D):** 1500 x 1910 x 750 mm

**Weight:** max. 350 kg

**Power supply:** 3/N/PE AC 400/230 V, 50 Hz

## INSTALLATION AND MAINTENANCE

The electrolyser system is shipped pre-assembled and pre-wired. On site just an electricity supply and operating water have to be connected and the sodium hypochlorite metering system has to be installed. For these works, the correct installation and regular maintenance, we recommend our specially trained technicians.



Auf der Weide 10, 89312 Günzburg, Germany

+49 (8221) 904-0 [www.evoqua.com](http://www.evoqua.com)

OSEC and Wallace & Tiernan are trademarks of Evoqua, its subsidiaries or affiliates, in some countries. Hastelloy is a trademark of Haynes International, Inc. All information presented herein is believed reliable and in accordance with accepted engineering practices. Evoqua makes no warranties as to the completeness of this information. Users are responsible for evaluating individual product suitability for specific applications. Evoqua assumes no liability whatsoever for any special, indirect or consequential damages arising from the sale, resale or misuse of its products.

© 2015 Evoqua Water Technologies GmbH Subject to change without notice WT.085.060.000.DE.PS.OSEC-B.0215

### Wallace & Tiernan® Products worldwide

#### Australia

+61 3 8720 6597  
info.au@evoqua.com

#### Bahrain

+973 39 78 66 54  
wtbah@evoqua.com

#### Canada

+1 905 944 2800  
canadainfo@evoqua.com

#### France

+33 1 41 15 92 20  
wtfra@evoqua.com

#### Germany

+49 8221 9040  
wtger@evoqua.com

#### Singapore

+65 6830 7165  
sales.sg@evoqua.com

#### UK

+44 1732 771777  
info.uk@evoqua.com

#### USA

+1 856 507 9000  
information@evoqua.com